




25-500: SQUARE PATTERN BRONZE WATER GAUGES

OVERVIEW

Available with 1/2" (ASTM B-16 brass bar stock) or 3/4" (B-584 cast bronze) NPT male pipe connections. Four guard rods and EPDM gauge glass gaskets standard. Other glass gaskets available. Automatic ball checks help prevent the loss of fluids should the glass be broken.



FEATURES

- Standard 1/4" needle drain valve in lower arm
- Pet cock or Apollo® ball valve drain on request
- Polished finish
- Ball checks standard
- Rated: 200 psig @ 400°F, 400 psig @ 100°F (See note!)
- CRN Registered

Part Number	Pipe Size (in.)	Glass O.D. & Length	Wt./100 (lbs.)	Wheel Type
25-501*	1/2	5/8 x 12	290	ALUMINUM
25-502*	1/2	5/8 x 12	290	COMPOSITION
25-504*	3/4	3/4 x 16	355	ALUMINUM
25-505*	3/4	3/4 x 16	355	COMPOSITION

Note: Service ratings are subject to pressure/temperature ratings of gauge glass and glass gaskets.
* Automatic ball valves

OPTIONS

Suffix Number	Specification
-00	Standard gauge w/ standard glass & rod
-01	Top only
-02	Bottom only
-03	Standard gauge less glass & rod
-10	For special gauges w/ non-standard glass and rod lengths